

FLUSH-DESIGN

System	Bibloc relocatable partition
Brief description	<p>Modular relocatable partition system based around a steel frame construction onto which are hooked, solid panel modules in a wide range of widths and finishes or double-glazed modules. The solid partitions is identical to the Flush-Line partition. The difference is in the glazed modules and door elements. The Flush-Design offers a contemporary design, where the visible profiles are minimized, all joints recessed, hinges invisible, creating a “flush” look and gives the effect of floating glass on an invisible frame.</p> <p>The Flush-Design partition is suitable in any utility building and is extremely convenient to create contemporary office spaces very quickly. Thanks to its limited number of components and clever construction relocation is achieved in the shortest time period.</p>
Fire rating	The Flush-Design glazed partition is available in standard not fire-resistant version and also in fire-resistant EI-30 version.
Sound Insulation	<p>Results following the European norms EN ISO 717-1 en EN ISO 140-3 :</p> <p>Solid partition Flush-Line chipboard 47dB Rw. Possible up to 51dB and 54dB Rw. Solid partition Flush-Line steel 52dB Rw. Possible up to 55dB Rw. Double glazed partition Flush-Design 46dB Rw. Possible up to 49 dB Rw.</p>
Stability	In conformity with the highest standards. Report available on request.
Thickness	100 mm
Heights	Floor to ceiling: up to 3.1m with full height panel. Higher is possible with horizontal joint.
Height Tolerance	up to 15 mm deviations in floor levels can be taken up by the system.
Partition Modules	The standard module width is 1200mm, other widths are also available on request.
Weight	Solid module: about 30 kg/m ² - double glazed module: about 40kg/m ²
Frame	<p>Inner frame in galvanised steel.</p> <p>Vertical C-section studs, with oblong-formed perforations to receive the panel-hooks, and whom can also offer different hook-on solutions for shelves, coat pegs, hook on cupboards and tables. These studs also have 30mm round perforations at 200mm centres to allow for continuous wiring routs.</p> <p>The floor track (80 x 62,5 x 80) and the ceiling track (60 x 62,5 x 60) are also manufactured from U section galvanised steel, with slotted oblong perforations in the base to take structural fixings. These head and base tracks are powder coated and form a recessed head and skirting detail. Both the stud on the panel carrying sides and the floor and ceiling tracks on the base side has closed cell foam strips to aid acoustic insulation.</p>
Solid Modules	<p>The standard panels are classified from Class A, E1, 18mm Chipboard with a density of 650 kg/m³. These panels can be finished in various coverings, such as fabric and vinyl wall coverings, melamine, HPL laminate or natural wood veneers. On the 4 edges the panels are finished in the same colour as the front side. Panel hooks are fixed to the back of the panel, and are then hooked on to the perforated structural stud. These panels can are also available in MDF, Plywood or Class O Chipboard.</p> <p>Steel panels are also available. The steel cassette is folded from 1mm thick steel and powder coated in a RAL colour of choice. On the inside a chipboard or plasterboard panel is inserted.</p>
Insulation	Standard modules have 60mm, 45kg/m ³ density, Rockwool batts. In the vertical studs and floor and ceiling track Rockwool batts of 150kg/m ³ are inserted. In combination with the foam strips they offer an optimal sound insulation.

Doorframes	Aluminium flush doorframes are fitted with hidden 'SOSS' hinges. All doorframes are pre-assembled and machined ready to receive ironmongery and fitted with acoustic gaskets. Wooden frames are also available. In case of double glazed doormodules the aluminium doorframe has glass glued on one side.
Door leaf	Standard widths are 830 and 930mm. Standard heights are 2015mm, 2115mm. Other dimensions are possible. By default the leaves are equipped with 0.8mm thick HPL laminate. Of course traditional wood veneers or painted doors are also available. Full single glazed doors are available in 8 or 10mm toughened glass. Double glazed doors with frameless glass are also available. In this case the door leaf thickness is 100mm. For solid door the thickness is always 50mm. Full height doors are available on any door type.
Ironmongery	All door handles, locks, door stops and hinges available on request. By default an L or U-shaped handle in stainless steel 19mm diameter is included. The standard door stop is also in stainless steel.
Glass Modules	Bibloc system, comes as finished manufactured double glazed units in 8mm laminated or toughened glass. The unique design of the flush-glazing units, gives the effect of floating glass on an invisible frame. The glass has a coloured 30mm boarder hiding the fixing method form glass to aluminium frame. The glass is polished on its perimeter. These units also have factory fitted panel hooks (which remain completely adjustable in height thanks to a continuous groove in the vertical profile) on the long legs, which hook on to the structural studs. In the EI-30 fire-resistant version an extra fire-rated glass is installed in the centre of the partition. All sorts of glass are possible. Sandblasting and every type of film are available. Venetian blinds are incorporated between the double-glazing, and are handled manually or electrically. A combination with Flush-Line window frames is always possible. On one side the standard Flush-Line unit, with visible 30mm aluminium frames, on the other side the Flush-Design frameless glazing. All modules are perfectly exchangeable. Switching a solid module with a door or glazed module is very easy.
Coating	All visible profiles i.e. skirting, corners, wall abutments, door and window frames, are powder coated and available in any RAL colour. All coating is done with a polyester powder coating of minimum 60 microns.
Accessories	Shelves: by the means of ledges, which are hooked in the middle perforations of the studs, shelves are easily attached to the partitions, without damaging the panels. The shelves are available in the same finishing as the panels, glazed shelves are also available. The shelf-hooks are also available in any Ral polyester coating. Hooks to attach pictures, coats, etc. are also available.

* * * *

PAN-ALL withholds the sole right to bring modifications to any description or detail at any time, without any prior notice - edition March 2011.

